Installation Instructions



Light Bar Instructions for 2006-13 Toyota FJ Cruiser

Part# 30761



*Note: picture may not reflect actual product.

Step 1: Locate the bracket marked "DS" (driver side). Starting with the driver's side, locate the two bumper bolt locations on the frame horn and loosen the left 14mm hex head nut half way. Next, take the driver side bracket and slide the $\frac{1}{2}$ " notched portion of the bracket down over the 14mm frame bolt and hand tighten. Next, take a $\frac{3}{8}$ " x 4 $\frac{1}{2}$ " hex bolt, $\frac{3}{8}$ "" flat washer and start from the bottom side of the bumper bracket and go through until the bolt is through the light bar bracket on top. Add the $\frac{3}{8}$ " hex nut, $\frac{3}{8}$ " flat washer on top and hand tighten. See Figure 1

Figure 1



Figure 2



Installation Instructions

Step 2: Trim out a 1" slot in the plastic mesh on both sides of the bumper (see Figure 2). This will allow the light bar brackets to slide through and match up with the brackets on the bumper mount.

Step 3: Carefully slide the light bar through the 1"inch slotted hole in the bumper until the four brackets align. Next, start the two 3/8"x 1" hex bolts and 5/16" washers in each bracket and hand tighten. Then start the two 5/16" x 1" carriage bolts, 5/16" washers and 3/8" hex nuts in each bracket and hand tighten.

Step 4: After the final adjustment, torque each bolt location to 15-20 ft/lbs. This concludes the installation.

Warranty

PIAA Corp. USA warrants its products to be free from defects in workmanship and materials under normal use for a period of one year from the date of purchase.

EXCLUSIONS

This limited warranty specifically excludes defects resulting from misuse, abuse, neglect, alterations, modification, improper installation, unauthorizes repairs, theft, vehicle crash, or any other type of impact. Except for the limited warranty stated above, there are no warrantied of PIAA products or part thereof, whether express or implied. Any implied warranty of merchantability or any warranty of fitness for a particular purpose is expressly disclaimed. Some states do not permit the disclaimer of implied warranties.

EXCLUSION OF DAMAGES

In no event shall PIAA be liable for any damages whatsoever (including, without limitation, consequential damages, incidental damages, or damages for loss of use, loss business profits, business interruption, loss of business information, loss of time, inconvenience, or other losses) arising out of the use, misuse, or inability to us a PIAA product. PIAA reserves the right to change the design of its products without any obligation to modify and previous products. This warranty give you specific legal rights. You may also have other rights that vary from state to state.

REPAIR AND REPLACEMENT

If a PIAA product is suspected of being defective, it must be submitted freight prepaid, to either an authorized dealer or distributor for warranty inspection. The receipt or other proof of purchase and a description of the problem must included. The returned product will be inspected. If the product is found to be defective and covered by this limited warranty, the sole remedy is repair or replacement, at PIAA's option. A repaired or replacement product will be shipped back at no charge, and will be warranted free from defects in workmanship and materials under normal use as the original purchaser owns it. Removal, installation, or re-installation costs are not covered by this limited warranty.

PIAA CORPORATION, USA
3004 NE 181st Avenue Portland, Oregon 97230
Telephone: 503.489.6666 - Fax: 503.489.6600 - Web: www.piaa.com